



# Structural Fill SE350

## Standard Specification Clause

Sundolitt Structural Fill SE350 Expanded Polystyrene (EPS). Large blocks of EPS with flame retardant additive for use as a lightweight fill in civil engineering applications. Manufactured and tested in accordance with BS EN 14933.

Compressive strength	350 kPa at 10% nominal compression
Design Load	140 kPa at 1% nominal compression
Thermal conductivity	0.033 W/mK
Block size	2400 x 1200mm


For the full range of physical properties please see our Structural Fill Datasheet on our website : [www.sundolitt.com/en](http://www.sundolitt.com/en)

### Structural Fill SE350

- Manufacturer: Sundolitt Ltd
- Website: [www.sundolitt.com/en](http://www.sundolitt.com/en)
- Email: [enquiriesuk@sundolitt.com](mailto:enquiriesuk@sundolitt.com)
- Tel: +44 (0)1786 471586
- Fax: +44 (0)1786 464825
- Address: Sundolitt Ltd,  
Suite A2 Stirling Agricultural Centre,  
Stirling. FK9 4RN
- Product reference: Structural Fill SE350
- Thickness: 600 mm / 300 mm / 150 mm / 100 mm

### Accreditation

Sundolitt Structural Fill SE350 EPS Blocks are manufactured in accordance with BS EN 14933 under Quality Control and Environmental Management Systems.



### CONTACT US

 01786 471586

 [enquiriesuk@sundolitt.com](mailto:enquiriesuk@sundolitt.com)

 [www.sundolitt.com/en](http://www.sundolitt.com/en)