

# U Value Request

## Ground Floor

Sundolitt provide free-of-charge U value calculations and condensation risk analyses. This service is to help you confirm compliance with current Building Regulations when using our products for your construction project.

Our Ground Floor U value calculations are carried out in accordance with BS 13370 and the guidance in BR 443 – Conventions for U Value Calculations. To provide this service we require some detailed information regarding the construction. The floor area and perimeter are measured to the internal face of external walls. Exposed Perimeter includes floor edges adjacent to unheated spaces such as garages and porches.

Please complete this form and click on the **SUBMIT FORM** button at the end to e-mail your request direct to us

### Contact Information

Contact Name :

Company Name :

E-mail Address :

Telephone :

Address :

Postcode :

Project Name :

Project Address :

Project Type :      New Build          Refurbishment          Extension      
                                 Domestic          Non-Domestic/Commercial   

Project Stage :

U Value Required:

Or Insulation Specified/Used :

Floor Area :

Length of Exposed Perimeter :

Floor Construction (From Ground Up - excluding hardcore) : (additional layers can be added on the following page)

	DESCRIPTION	THICKNESS (mm)
Layer 1 :		
Layer 2 :		
Layer 3 :		
Layer 4 :		
Layer 5 :		

### CONTACT US

# U Value Request

## Ground Floor

Project Name :

	DESCRIPTION	THICKNESS (mm)
Layer 6:		
Layer 7:		
Layer 8:		
Layer 9:		
Layer 10:		
Layer 11:		
Layer 12:		
Layer 13:		
Layer 14:		
Layer 15:		
Layer 16:		
Layer 17:		
Layer 18:		
Layer 19:		
Layer 20:		

Please provide any additional information we should be aware of for the purpose of this calculation :

### CONTACT US